



Find the Look

Find the way ►►►

With Vision Digital Signage

DSD 55" 4K Digital Signage Display

Introducing Vision's first Digital Signage Kiosk, built to help integrators customize the perfect information display for each project. From retail stores to corporate offices and beyond, this industrial-grade solution is quick to set up, easy to connect, and has completely open architecture to fit in any digital signage network.

Elevate your message with the ultimate visual innovation. The whole front face is glass, completing the full integration of the display and chassis, distinct from the typical bulky AV totems.

Easy Setup

This product has been given the trademark VISION treatment to make assembly and operation as easy as possible. If you can install a TV you can set this product up.

Razor-Thin

Just 22.3 mm thick and featuring a display that extends close to the edges, this kiosk represents the forefront of design. Gently rounded edges enhance the quality of the fit and finish.

Built-in Audio

Integrated speakers featuring a 2 x 5W amplifier at 8 ohms.

Professional display

This high-grade display is built to last beyond 50,000 hours. It lacks a built-in media player or internal operating system, so you will need to connect a PC or media player via the HDMI port.

Lockable Storage

To access the input ports and install a media player, open the back door.

Remote Control

The package includes a full-featured IR remote.

VISION

DIGITAL SIGNAGE

DSD-55 55" 4K Digital Signage Display




Slim & sleek design



All the right connections



Flexible set up



Crystal clear picture & sound



Specifications

Dimensions display

1960mm(h) x 764mm(w) x 450mm(d) /
77"(h) x 30"(w) x 18"(d)

Carton dimensions

1950mm(h) x 875mm(w) x 225mm(d) /
77"(h) x 34"(w) x 9"(d)

Product weight

54 kg / 119 lb

Packaged weight

58 kg / 128 lb COLOUR Black INPUTS 2 x HDMI
1 x DisplayPort 1 x USB (for upgrades)

Audio output

Integrated 2 x 5 Watts RMS @ 8 OHMS amplifier
with speakers 1 x 3.5mm Minijack Audio
line-level output

Operating temperature

0 - 40°C / 32 - 104°F

Power consumption

On: 96 W Standby: 1.4W

Accessories included

1 x UK IEC power cable 1.8m long 1 x EU IEC
power cable 1.8m long Remote Control

Power supply

110-240V 50/60 Hz

Warranty

1 Year - Excluded from Vision Standard Lifetime

Compliances

RoHS, WEEE, CE/EMC, CE/LVD, UKCA Industrial
55" BOE panel

Frame rate

50-60 Hz

Native resolution

3840 x 2160 4K ASPECT RATIO 9:16

Brightness

350 cd/m2

Viewing angle

H: 178° v: 178°

Light source rating

50,000 hrs

Manufacturer part number

DSD-55 [SAP: 10518479]

Operating humidity

10-80% RH

Storage temperature

Recommended: 5°C - 40°C / 41 - 104°F
Max: -10°C - 60°C / 14 - 140°F